Aluminium alloys ingots for remelting

ALLOY DATA SHEET

ALLOY GROUP ¹		NUMERICAL DESIGNATION ¹			1 ¹	CHEMICAL DESIGNATION ¹					S.A.V. ALLOY CODE			
AlSi7Mg			EN AB - 42200)	EN AB-Al Si7Mg0,6					01011156		
				¹ EN	1676:2020 A	luminium an	d aluminiu	m alloys – A	lloyed ingots	for remelting	g – Specifica	tions		
					NGOT	S CHE		L CO	MPOS	ITION				
Alloy	% _{wt}	Si	Fe	Cu	Mn	Mg	Cr	Ni	Zn	Pb	Sn	Ti	Other Each	Other Total
EN AB -	Min.	6,5	-	-	-	0,50	-	-	-	-	-	-	-	-
42200 ¹	Max	7,5	0,15	0,03	0,10	0,70	-	-	0,07	-	-	0,18	0,03	0,10
				¹ EN	1676:2020 A	luminium an	d aluminiu	n alloys – A	lloyed ingots	for remelting	g – Specifica	tions		

	CASTINGS CHEMICAL COMPOSITION													
Alloy	% wt	Si	Fe	Cu	Mn	Mg	Cr	Ni	Zn	Pb	Sn	Ti	Other Each	Other Total
EN AC -	Min.	6,5	-	-	-	0,45	-	-	-	-	-	-	-	-
42200 ²	Max	7,5	0,19	0,05	0,10	0,70	-	-	0,07	-	-	0,25	0,03	0,10
			2 F	N 1706.202	20 Aluminiun	n and alumin	ium allovs	- Castings -	- Chemical co	omposition a	nd mechani	cal properties		

			PERTIES ²
MEGH	ANICA	L PNUP	ENHES

Minimum mechanical properties for separately cast sample										
Casting method	Temper designation	Tensile strength R _m [MPa] min.	Yield strength Rp0,2 [MPa] min	Elongation A [%] min	Brinnell hardness HBW min					
Sand Casting	Т6	250	210	1	85					
Chill Cooting	Т6	320	240	3	100					
Chill Casting	T64	290	210	6	90					
Law Pressure die Costing	Т6	320	240	3	100					
Low Pressure die Casting	T64	290	210	6	90					
Investment Casting	Т6	290	240	2	85					
Pressure die Casting	-	-	-	-	-					
Potential mechanical properties of test specimens from castings ³	_4	315	240	8	100					

²EN 1706:2020 Aluminium and aluminium alloys – Castings – Chemical composition and mechanical properties

³It cannot be assumed that the given values can be reached throughout the casting since mechanical properties strongly depend on the solidification rate, the heat treatment and the soundness of the casting. Therefore, the values and the position of the area where those values can be achieved shall be agreed between supplier and customer. ⁴ The heat treatment has to be defined according to the type of casting produced.

PHYSICAL PROPERTIES ²										
e	SAND CASTING		•		MACHIN	-				
METHO	PERMANENT MOULD CASTIN	•		MACHINA	MACHINABILITY AFTER HEAT TREATMENT					
CASTING METHOD	PRESSURE DIE CASTING	-		RE	SISTANCE TO CO	RROSION	В			
C	INVESTMENT CASTING	~	TIES		DECORATIVE ANODIZING					
~	FLUIDITY	В	DTHER PROPERTIES		ABILITY TO BE WELDED					
CASTABILITY	RESISTANCE TO HOT TEARIN	Α	THER P		ABILITY TO BE POLISHED					
CAS	PRESSURE TIGHTNESS	В	ö	LIN	22					
IIES	STRENGTH AT ROOM TEMPERA	TURE	Α		ELEC	ELECTRICAL CONDUCTIVITY [MS/m]				
MECHANICAL PROPERTIES	STRENGTH AT HIGH TEMPERATURE					THERMAL CONDUCTIVITY [W/(m K)]				
NICAL	DUCTILITY (SHOCK RESISTAN	Α								
MECH	FATIGUE RESISTANCE [MPA]	80 - 110								
✔ In	 Indicates the most commonly casting process used for each alloys A: Optimal 				C: Fair	D: Poor	E: Not Recommended	F: Unsuitable		
	² EN 1706:2020 A	luminium and alumi	nium alloys – Cast	ings –	Chemical composition	and mechanical prop	erties			

S.A.V. S.p.A. Società Alluminio Veneto REGISTERED OFFICE: VIA COLOMBO, 5 35010 TREBASELEGHE (PD) ITALY TEL. +39 049 9386191 FAX 049 9387828 E-MAIL: <u>info@sav-al.com</u> WEB: www.sav-al.com Page 1/2

COMPANY WITH MANAGEMENT SYSTEM CERTIFIED

= ISO 9001 = = IATF 16949 =

COMPANY WITH MANAGEMENT SYSTEM CERTIFIED = ISO 14001 = = ISO 45001 = = ISO 50001 =

VERIFIED ENVIRONMENTAL MANAGEMENT **EMAS** IT-00184

S.A.V. S.p.A Società Alluminio Veneto

Aluminium alloys ingots for remelting

	HEAT TREATMENT DESIGNATION ²								
ABBREVIATION	HEAT TREATMENT								
F	AS CAST								
0	ANNEALED								
T1	CONTROLLED COOLING FROM CASTING AND NATURALLY AGED								
T4	SOLUTION HEAT TREATED AND NATURALLY AGED WHERE APPLICABLE								
T5	CONTROLLED COOLING FROM CASTING AND ARTIFICIALLY AGED OR OVER-AGED								
T6	SOLUTION HEAT TREATED AND ARTIFICIALLY AGED								
T64	SOLUTION HEAT TREATED AND ARTIFICIALLY UNDER-AGED								
T7	SOLUTION HEAT TREATED AND ARTIFICIALLY OVER-AGED (STABILIZED)								
	² EN 1706:2020 Aluminium and aluminium alloys – Castings – Chemical composition and mechanical properties								

CORRELATION WITH OTHER STANDARDS EN AB - 42200 / EN AC - 42200											
NATION	U.S.A.	JAPAN	INTERNATIONAL	ITALY	FRANCE	GERMANY	GREAT BRITAIN				
STANDARD	B179	H2211	17615	UNI	NF A57-702	1725	BS 1490				
STATUS	ACTIVE	ACTIVE	ACTIVE	SUPERSEDED	SUPERSEDED	SUPERSEDED	SUPERSEDED				
IDENTICAL INGOT STANDARD SPECIFICATION		-	Al Si7Mg0.6	-	-	-	-				
SIMILAR INGOT STANDARD SPECIFICATION	357.1 A357.2 B357.2 C357.2 366.1	-	-	UNI 8392	A-S7G0.6	GB-AISi7Mg	LM25				

Any dissemination, copy or reproduction of this document, even if only for extract, is prohibited.

The physical and mechanical properties shown in this data sheet have a mere informative purpose since they are detected on sample cast separately in specific cooling conditions. No liability is accepted for decisions based on the indicated physical and mechanical properties and no guarantee is given for the physical and mechanical properties indicated, as they depend on the specific conditions of casting of the cast pieces.

 Page 2/2

 S.A.V. S.p.A.
 COMPANY WITH MANAGEMENT
 COMPANY WITH MANAGEMENT
 VERIFIED ENVIRONMENTAL

 Società Alluminio Veneto Recistered Orfice:
 COMPANY WITH MANAGEMENT
 SYSTEM CERTIFIED
 VERIFIED ENVIRONMENTAL

 VIA COLOMBO, 5
 SYSTEM CERTIFIED
 = ISO 9001 =
 = ISO 14001 =
 EMAS

 Stor TREBASELEGHE (PD) ITALY TEL + 39 049 9386191 FAX 049 9387828
 = IATF 16949 =
 = ISO 50001 =
 EMAS

 E-MALL : info@sav.al.com
 WEB: www.sav-al.com
 IT-00184
 IT-00184